



9' x 7' 3285 white with optional white aluminum full-view window section

These models are also available in



DURABLE. RELIABLE.

SPECIFICATIONS, OPTIONAL FEATURES AND ACCESSORIES



EXHAUST PORT

An exhaust port is an optional feature to keep those unwanted fumes from lingering around the work area.



INSIDE SIDE LOCK


The inside side lock is a wise decision for added security when you are not around. (Torsion only)

OPTIONAL WINDOW DESIGNS

24" SECTION HEIGHT




24" x 6"



24" x 12"



34" x 16"



Full-View

COLOR SELECTION

WHITE*

ALMOND

SANDSTONE

BROWN

GRAY

BLACK

Note: Refer to samples at your local C.H.I. Distributor for exact color match.

*3282 available in white only.



Wind chamber tested to ensure wind load resistance, the C.H.I. Windbreaker Series and iSeries doors provide enhanced defense against the elements.

FEATURES

26-GAUGE **MODEL 3285** Insulated

24-GAUGE **MODEL 3282** Insulated

SECTIONS

- Features four evenly spaced micro-grooves that run horizontally across each section
- Double-sided steel doors are 24 or 26-gauge front and 27-gauge back for sturdiness
- Concealed steel back-up plates run from top to bottom of each section for secure hardware attachment
- Section joints are tongue-and-groove
- White painted end stiles
- Bottom "U" type astragal is a standard feature
- 3285 is available in white, almond, sandstone, brown, gray, or black; 3282 is available in white only

TRACKS

- Tracks are 2" or 3", as specified
- Available in bracket mount, angle mount, clip angle mount, 12" radius, 15" radius, high lift, vertical lift, roof pitch, or dual track low headroom

HARDWARE

- Package includes 11-gauge or 14-gauge hinges, as specified
- 2" or 3" long-stem or short-stem steel ball bearings rollers
- Heavy-duty adjustable top roller brackets

SPRINGS

- Torsion springs are helically wound with stress relieved, oil-tempered wire
- Springs are individually-calibrated for each door
- Counter-balance torsion shafts are galvanized for rust resistance
- High cycle spring options may be specified

INSULATION TYPE

- CFC free polystyrene core is secured in place with a urethane adhesive to increase structural integrity
- R-value - 10.29



DOOR CONSTRUCTION

CFC free polystyrene insulation is secured in place with a urethane adhesive to increase structural integrity. The front and back skins are locked together in a tongue and groove design for years of worry free protection.

Model 3285..... R-value* - 10.29